



## 24-PORT GbE MULTILAYER SWITCH WITH FOUR 10 GbE/HiGig+™ PORTS


### FEATURES

- 24 10 Mbps/100 Mbps/1000 Mbps Ethernet ports, supporting both copper and fiber connections
- Fifth generation of StrataSwitch® and StrataXGS® product lines
- Four 12 Gbps or 10 Gbps HiGig+™ port uplink interfaces
- Four 10 GbE switching ports, CX4 support
- Line-rate switching for all packet sizes and conditions
- On-chip data packet memory and table memory
- IPv6 routing and tunneling
- Advanced Fast Filter Processor (FFP) ContentAware™ classification
- Advanced security features in hardware
- Port trunking and mirroring supported across stack
- Advanced packet flow control:
  - Head-of-line blocking prevention
  - Backpressure support
- Eight Quality of Service (QoS) queues per port with hierarchical minimum/maximum shaping per Classes of Service (CoS) per queue per port
- Standard compliant IEEE 802.1ad provider bridging


### SUMMARY OF BENEFITS

- Highly scalable BroadScale™ processor evolved from five generations of switching experience provides rich features, scalability, and future-proof solutions.
- Optimized for secure-switching and convergence of applications and services in the networks.
- System vendors can build scalable high-performance, high-port density GbE LAN switches in several form factors.
- Multiple CoS and low latency enable the support of VoIP and other voice, video, and data applications.
- Built-in high-speed serial interfaces with Broadcom-unique SerDes technology ease and accelerate system design, while reducing cost and conserving board space.
- Broadcom switch API compatibility enables software reuse and faster time-to-market.
- Small package and low power enable cost-effective and high-performance system design.


24-Port Gigabit Ethernet Multilayer Switch



## OVERVIEW



24 10/100/1000 + Two 10 GbE + Two HiGig+ Stackable



48 10/100/1000 + Two 10 GbE + Two HiGig+ Stackable

The BCM56504 is the fifth generation of the highly integrated and cost-effective StrataSwitch and StrataXGS product line. The BCM56504 is a single-chip solution with 24 GbE ports and four 10 GbE/HiGig+ uplink ports.

The BCM56504 incorporates 24 GbE ports that can operate 10 Mbps/100 Mbps/1000 Mbps. The uplink ports can operate in two modes: 10 GbE switching mode and HiGig+ uplink mode. The integrated 10 GbE switching ports are CX-4-compliant XAUI™ interfaces. The HiGig+ uplink interface is used to connect to other StrataXGS devices in a larger stacking system or to the BCM5675/BCM5676 Switch Fabric via a backplane in a multislot redundant chassis system.

With high-integration and high-port density, the BCM56504 family is ideal for Enterprise applications in stand-alone, stackable, and chassis configurations applicable in the edge, aggregation, and core areas of the Enterprise. The BCM56504 is also ideal for embedded switch applications like Blade Server Switch, ATCA chassis, IPDSLAM, 3G Wireless Base Station, and others.

The BCM56504 integrates sophisticated advanced L3 switching features for cost-effective highly manageable Enterprise networks. The BCM56504 performs IPv6 routing and transition services in hardware, allowing IT managers to deploy L3 switches that are future-proof, highly manageable L3 networks to enable cost-effective transition from IPv4 to IPv6.

The ContentAware classification feature of the StrataSwitch and StrataXGS has been further enhanced in the BCM56504 with unmatched flexibility and programmability. The ContentAware engine can be used for applications such as policy-based routing, access control list, dynamic adaptation to changes in virus threats, and so on.

The BCM56504 has built-in security functions for highly secure Enterprise networks including BroadSAFE™. Utilizing hardware-based identity management and authentication coupled with key management software that directs and manages clients, BroadSAFE security provides exceptionally strong network security without impacting network performance.

The BCM56504 integrates sophisticated metering, statistics, and traffic management features, optimizing the QoS in the Enterprise networks for voice, video, and data convergence. The BCM56504 also provides rate-adjustable, hardware-based sFlow® implementation and flexible multiple-session remote port-mirroring functionality for efficient network management.

The BCM56504 switch supports a BSC controller for communicating with external devices such as serial EEPROM, flash PROM memories, and parallel port devices. The BCM56504 also supports a serial interface for the MII management of physical layer devices.

The BCM56504 switch interfaces to a host CPU via a 32-bit PCI bus, running at up to 66 MHz. Bus mastering and advanced DMA are supported for efficient exchange of packet data between the CPU memory and the BCM56504 switch.

**Broadcom®**, the pulse logo, **Connecting everything®**, the Connecting everything logo, StrataSwitch®, StrataXGS®, ContentAware™, BroadScale™, HiGig+™, and BroadSAFE™ are trademarks of Broadcom Corporation and/or its affiliates in the United States, certain other countries and/or the EU. Any other trademarks or trade names mentioned are the property of their respective owners.

Connecting  
**everything®**



BROADCOM CORPORATION  
5300 California Avenue,  
Irvine, California 92617

© 2009 by BROADCOM CORPORATION. All rights reserved.

56504-PB04-R 09/24/09

Phone: 949-926-5000  
Fax: 949-926-5203  
E-mail: [info@broadcom.com](mailto:info@broadcom.com)  
Web: [www.broadcom.com](http://www.broadcom.com)